



ORDERING STRING

F-SERIES 40

INNOVATION DOWN TO THE LAST DETAIL



F **P** **40** **E** **20** **3** **D**



VERSION

F = retractable locating pin package with dual rod

OPERATION

P = pneumatic

SIZE

40 = Ø 40 mm mounting pattern 35x25 mm
41 = Ø 40 mm mounting pattern 30x25 mm

SENSOR

E = electronic sensor with M12 swivel connector - PNP
A = electronic sensor with M12 swivel connector - NPN
N = no sensor
B = electronic sensor with M8 swivel connector - PNP

STROKE

20 = 20 mm
40 = 40 mm

ROD TERMINATION

1 = rod termination type 3 with improved radius
2 = rod termination type 7 with improved radius
3 = rod termination for offset pins
7 = rod termination for offset pins - with 4 dowel holes (see datasheet)

PORTS

G = GAS
D = dual GAS ports on rear end cap



Subject to change without notice



ORDERING STRING

F-SERIES 63

INNOVATION DOWN TO THE LAST DETAIL



F **P** **63** **E** **60** **3** **D**



VERSION

F = retractable locating pin package with dual rod

OPERATION

P = pneumatic

SIZE

63 = $\varnothing 63$ mm

SENSOR

E = electronic sensor with M12 swivel connector - PNP
A = electronic sensor with M12 swivel connector - NPN
N = no sensor
B = electronic sensor with M8 swivel connector - PNP

STROKE

15 = 15 mm
25 = 25 mm
40 = 40 mm
50 = 50 mm
60 = 60 mm

ROD TERMINATION

1 = rod termination type 3 with improved radius
3 = rod termination for offset pins

PORTS

G = GAS
D = dual GAS ports on rear end cap



Subject to change without notice