



ORDERING STRING HE-SERIES



HE 1 P 1 E G 1 A 01

VERSION

HE = High Efficiency clamp

MOUNTING PATTERN STANDARD

1 = European mount
2 = NAAMS mount



OPERATION

P = pneumatic

SIZE

0 = housing size 40 / cylinder Ø 32 mm
1 = housing size 50 / cylinder Ø 40 mm
2 = housing size 63 / cylinder Ø 50 mm
3 = housing size 80 / cylinder Ø 63 mm

SENSOR

E = electronic sensor
with M12 swivel
connector - PNP

N = no sensor

A = electronic sensor
with M12 swivel
connector - NPN

B = electronic sensor with M8
swivel connector - PNP

PORTS

G = GAS
N = NPT

ARM MOUNT



ARM MATERIAL

A = aluminum
S = steel

CLAMP ARM TYPE

01 = wishbone, central, 15 mm offset, Ø 6H7*

02 = wishbone, right, 15 mm offset, Ø 6H7*

03 = wishbone, left, 15 mm offset, Ø 6H7*

04 = wishbone, central, 45 mm offset, Ø 6H7

05 = wishbone, right, 45 mm offset, Ø 6H7

06 = wishbone, left, 45 mm offset, Ø 6H7

Please see the charts in the datasheets for arm position as well as for max. opening angle

NAAMS clamping arms to be ordered separately

*for size 3 → 20 mm offset

Subject to change
without notice

INNOVATION DOWN TO THE LAST DETAIL

